

**DESCRIPTION:**


The IS-SS-HID-I is an audio-only door station for the IS system, with a built in HID® iCLASS card reader.

The audio door station can be connected via CAT-5e/CAT-6 wire to any of the following IS exchange units: IS-CCU, IS-SCU, or IS-RCU. Maximum distance from the door station to the exchange unit is 980'.

Wiring and power for the card reader are separate from the intercom wiring. The card reader is to be connected to a host controller of any type that is compatible with the HID® iCLASS R10 (Rev.C) smart card reader.

**FEATURES:**

- Audio door station for IS System
- Stainless steel faceplate
- HID® iCLASS R10 (Rev. C) smart card reader built-in
- Tamper resistant screws



# IS-SS-HID-I

Stainless Steel Flush Mount Audio Door Station with HID® iCLASS Reader

## FEATURE CALL-OUT DEFINITIONS:

[1] Microphone

[2] Speaker

[3] Call button

[4] iCLASS R10 (Rev. C) reader

## SPECIFICATIONS:

Power Source: 48VDC (supplied from CEU)

Communication: Open voice hands-free

Wiring: CAT-5e or CAT-6

Wiring distance: 980'

Door release contact: 24V AC/DC, 500mA  
(N/O, COM, N/C)

Operating Temp: 14° - 140°F (-10° - 60°C)

Dimensions: 7" W x 12-<sup>3</sup>/<sub>8</sub>" H x 1-<sup>7</sup>/<sub>8</sub>" D

## FEATURE CALL-OUTS:

